

Dimensions of Reducing Fittings 20 x 18 through 48 x 22



Nom. Pipe Size	90 L.R. Reducing Elbows	Reducing Outlet Tees		Concentric & Eccentric Reducers
	A	C	M	H
20x18	30	15	14.5	20
20x16	30	15	14	20
20x14	30	15	14	20
20x12	30	15	13.62	20
20x10	30	15	13.12	
20x8		15	12.75	
22x20		16.5	16	20
22x18		16.5	15.5	20
22x16		16.5	15	20
22x14		16.5	15	20
22x12		16.5	14.62	
22x10		16.5	14.12	
24x22	36	17	17	20
24x20	36	17	17	20
24x18	36	17	16.5	20
24x16	36	17	16	20
24x14	36	17	16	
24x12	36	17	15.62	
24x10		17	15.12	
26x24		19.5	19	24
26x22		19.5	18.5	24
26x20		19.5	18	24
26x18		19.5	17.5	24
26x16		19.5	17	
26x14		19.5	17	
26x12		19.5	16.62	
28x26		20.5	20.5	24
28x24		20.5	20	24
28x22		20.5	19.5	
28x20		20.5	19	24
28x18		20.5	18.5	24
28x16		20.5	18	
28x14		20.5	18	
28x12		20.5	17.62	
30x28		22	21.5	24
30x26		22	21.5	24
30x24		22	21	24
30x22		22	20.5	
30x20		22	20	24
30x18		22	19.5	
30x16		22	19	
30x14		22	19	
30x12		22	18.62	
30x10		22	18.12	

Nom. Pipe Size	Reducing Outlet Tees		Concentric & Eccentric Reducers
	C	M	H
34x30	25	24	24
34x24	25	23	24
34x20	25	22	
34x16	25	21	
36x34	26.5	26	24
36x32	26.5	25.5	24
36x30	26.5	25	24
36x26	26.5	24.5	24
36x24	26.5	24	24
36x22	26.5	23.5	24
36x20	26.5	23	24
36x18	26.5	22.5	
36x16	26.5	22	
42x40	30	28	24
42x38	30	28	24
42x36	30	28	24
42x34	30	28	24
42x32	30	28	24
42x30	30	28	24
42x28	30	27.5	
42x26	30	27.5	
42x24	30	26	
42x22	30	26	
42x20	30	26	
42x18	30	25.5	
42x16	30	25	
48x46	35	33	28
48x44	35	33	28
48x42	35	32	28
48x40	35	32	28
48x38	35	32	
48x36	35	31	
48x34	35	31	
48x32	35	31	
48x30	35	30	
48x28	35	30	
48x26	35	30	
48x24	35	29	
48x22	35	29	

All dimensions given in inches for common diameters and wall thicknesses. Additional sizes may be available upon request. Dimensions in accordance with ASME B16.9. Other sizes, schedules and wall thicknesses also available.